



Certified ISO 9001:2015




DP61 / PR61

INTRODUCTION

DP61 / PR61 is the SUPERDURABLE powder coating solution developed by Protech-Oxyplast Group, utilizing their patented PR61 technology. **DP61 / PR61** is specially designed to ensure excellent resistance even in the harshest weather conditions.

DP61 / PR61 meets the highest architectural industry standards, fully complying with the stringent requirements of **Qualicoat 2** and **AAMA 2604**. It offers superior performance and long-lasting durability, making it an ideal choice for demanding applications.



| HOW DOES IT WORK?

DP61 / PR61 features a high-performance polyester resin known for its outstanding UV resistance, surpassing standard resins. This advanced formulation ensures superior color retention and excellent weather durability, delivering long-lasting performance.

DP61 / PR61 surpasses stringent standards such as **Qualicoat 2** and **AAMA 2604**, providing superior protection and durability for high-demand architectural applications.



MAIN FEATURES & ADVANTAGES



Gloss and color retention are preserved by over 30% under severe weather conditions according to AAMA 2604 standards.



Outstanding radiation durability, excellent resistance against UV light, and saponification.



Ideal chemical resistance capability.




Versatile coating solution: flexible applications for both indoor and outdoor uses.



Meets the performance criteria of AAMA 2604 and Qualicoat 2 standards.

| TYPICAL APPLICATIONS

OUTDOOR APPLICATIONS



Metal Architecture



Metal Windows and Rolling Doors




Architectural Structures



Satellite Dish



Heavy Industrial Equipment



Building Materials in Constructions



Automobile Industry

| COLOURS & SURFACE OPTIONS

Daiphu Protech-Oxyplast provides a wide range of readily available stock colors and surface options for customers to choose from. Please take a look at our color chart and get inspired from a broad range of extraordinary options. We also offer customized formulations to match your interests. Please contact our coating expert for further consultation and discussion.

| CARING AND MAINTENANCE

Daiphu Protech-Oxyplast strongly advises storing **DP61 / PR61** products in environments with consistent temperatures. Regular cleaning is recommended for items coated with **DP61 / PR61**, with inspection intervals based on local conditions, not exceeding 18 months. In coastal or harsh environments, cleaning should occur every 3 months. Please consult our usage guide for precise handling, storage, and maintenance instructions.

